

Key	Summary	Upgrade notes	Component/s
NXP-13744	Missing class org.apache.xerces.parsers.SAXParser	xercesImpl-*.jar has been moved from nxserver/lib/ to lib/	WebDAV / WSS
NXP-14113	NXP-14007 Extract the fulltext fields for indexing	New API CoreSession.getBinaryFulltext() returning a mapping of binary index field to text.	Elasticsearch, Search / Query
NXP-13925	Fix duplicate documents due to aclr_user duplicate rows	<p>IMPORTANT MIGRATION STEP</p> <p>Because the tables aclr_user and aclr_user_map may contain old duplicate rows now visible since NXP-13691, for databases that are upgraded the following must be executed:</p> <pre>DROP TABLE aclr_user; DROP TABLE aclr_user_map;</pre>	Core SQL Storage, Search / Query
NXP-14115	Include REST API in CoreServer	The REST API is now part of the core server. The Marketplace package nuxeo-rest-api does not exist anymore.	Rest API
NXP-13616	Improve file download on nuxeo api	<p>JsonDocumentWriter#writeDocument(JsonGenerator jg, DocumentModel doc, String[] schemas, Map<String, String> contextParameters, HttpHeaders headers) does not exist anymore it is replaced by :</p> <pre>JsonDocumentWriter#writeDocument(JsonGenerator jg, DocumentModel doc, String[] schemas, Map<String, String> contextParameters, HttpHeaders headers, HttpServletRequest request)</pre> <p>The generated JSON also changes and now includes a full URL to get the blob data :</p> <p>* Before :</p> <pre>{code} "file:content": { "name": "Nuxeo_Platform_5.8_administration_documentation.pdf", "mime-type": "application/pdf", "encoding": null, "digest": "4faa1208dbd8dce54db9174dabdec7db", "length": "11485973", "data": "files/80438e3b-48bb-42d1-9e08-9a0f54b8f945?path=%2Fcontent" }, {code}</pre> <p>* Now</p> <pre>{code} "file:content": { "name": "Meetup Docker.pdf", "mime-type": "application/pdf", "encoding": null, "digest": "f829ff57c289b60be5dd2c57adcf1d51", "length": "5980167", "data": "http://localhost:8080/nuxeo/nxbigfile/default/e596bd67-aaa5-4a43-a84c-bcf4850c4834/file%3Acontent" }, {code}</pre>	Rest API
NXP-13937	Add a widget template for sub images	widget template has been added at /widgets/image_subwidget_template.xhtml	Layouts & Widgets

Key	Summary	Upgrade notes	Component/s
NXP-13826	Improve release scripts with commit message and unique build	Customized commit messages used for all commits. New command "onestep" to prepare + perform (push and deploy) in one step. New option "--dryrun": improved dry run mode (previously only used via the "test" command).	Infrastructure
NXP-13800	VCS: auto-generated integer ids on Oracle	To activate, use in nuxeo.conf: nuxeo.vcs.idtype=sequence Or if you want to use another sequence than the default (HIERARCHY_SEQ), use: nuxeo.vcs.idtype=sequence:YOUR_SEQUENCE_NAME	Core SQL Storage
NXP-11551	Allow merged contributions for the repository config	Configuration for repositories is now of the form: <pre><extension target="org.nuxeo.ecm.core.storage.sql.RepositoryService" point="repository"> <repository name="default" factory="org.nuxeo.ecm.core.storage.sql.ra.PoolingRepositoryFactory"> <schema> ... </schema> <indexing> ... </indexing> ... (see http://doc.nuxeo.com/x/hwQz) </repository> </extension></pre> When several contributions are made to the same repository name, they are merged. The old syntax that contributed to two extension points, org.nuxeo.ecm.core.api.repository.RepositoryManager (repositories) and org.nuxeo.ecm.core.repository.RepositoryService (repository) is still supported for backward compatibility but will emit a WARN message. The two nested <repository> elements on the old extension point org.nuxeo.ecm.core.repository.RepositoryService can be merged, and the label="..." that was previously on the org.nuxeo.ecm.core.api.repository.RepositoryManager extension point can be added as an attribute to the new <repository> element.	Core SQL Storage
NXP-10182	Optionally use SQL arrays to store lists on PostgreSQL	A given list field can be switched to database array storage using: <pre><schema> <field type="array">some:field</field> </schema></pre> To automatically enable database arrays for all list fields, use: <pre><schema> <arrayColumns>true</arrayColumns> </schema></pre>	Core SQL Storage
NXP-14140	Make CoreSession thread-safe	It's now possible to use the same CoreSession over and over in different transactions, and pass it between threads. Some constraints remain: - it has to be closed properly, - it has to be used inside a transaction.	Core
NXP-14118	Make sure the junit tests are run with user 'system'	This impacts the junits runs. Now the principal 'Administrator' for the session injected in the tests as: @Inject protected CoreSession session; is an administrator: ((NuxeoPrincipal)session.getPrincipal()).isAdministrator() returns 'true';	Core
NXP-14049	Allow setting perDocumentQuery=false through type service	Instead of setting it through the repository reconfig, it's now possible (and recommended) to specify in the facet definition using the type service that a query on the facet (NXQL: ecm:mixinType = ...) will never need to match per-document facets. So instead of, in default-repository-config.xml, having:	Core, Core SQL Storage

Key	Summary	Upgrade notes	Component/s
		<pre data-bbox="572 190 864 280"><neverPerDocumentFacets> <facet>SomeFacet</facet> <facet>OtherFacet</facet> </neverPerDocumentFacets></pre> <p data-bbox="572 303 1118 332">You should use in the extension point defining the facet:</p> <pre data-bbox="572 354 1350 505"><extension target="org.nuxeo.ecm.core.schema.TypeService" point="doctype"> <facet name="SomeFacet" perDocumentQuery="false"/> <facet name="OtherFacet" perDocumentQuery="false"> <schema name="someschema"/> </facet> </extension></pre>	
NXP-13649	Configure PathSegmentServiceDefault maxSize through property	New framework property: nuxeo.path.segment.maxsize	Core
NXP-13148	Clean up session management	<p data-bbox="572 685 1341 736">To acquire a CoreSession (which should rarely be done in any case), you should now use the following pattern:</p> <pre data-bbox="572 759 1325 842">try (CoreSession session = CoreInstance.openCoreSession(repositoryName)) { // do something with session, including session.save() }</pre> <p data-bbox="572 864 1341 916">To do an explicit close if try-with-resource is not used as above, you should just call:</p> <pre data-bbox="572 938 737 968">session.close();</pre> <p data-bbox="572 990 1341 1042">CoreInstance has a few other openCoreSession signatures to acquire a session for a given user or a system session.</p>	Core
NXP-13842	Tooltips > Replace jquery tooltips by tipsy tooltips	<p data-bbox="572 1111 1325 1163">From 5.9.3, Nuxeo does not embed jquery tooltip library anymore. It has been moved to nuxeo-resources-compat.</p> <p data-bbox="572 1163 864 1192">Default tooltip library is tipsy.</p> <p data-bbox="572 1192 1341 1244">To enable a tooltip on any DOM element, specify the tooltip content in the 'title' attribute and add 'tipsyShow' css style class.</p>	Content Views, Ergonomics & UX
NXP-13877	Admin Center > Update connect icons and listing colors	delete galaxy_admin_logo.png and 100px_loading.gif	Admin Center, Style & CSS